



BIENFANG® Vacuum Presses

The preferred choice of professionals, BIENFANG® Vacuum Presses are easy to use and are backed by a track record of consistent, outstanding performance. Guaranteed quality results every time for mounting, laminating and texturing projects.

Vacuum Press Features

- Touch-pad controls assure consistency and are user friendly
- Easy-read digital displays
- Programmable System Controller with 6 factory-installed programs for temperature and dwell time
- End-of-cycle signal
- Sturdy Dura-Box alloy frame provides a tight vacuum seal and extra durability
- Space-saving work surface
- Maintenance-free vacuum pump

The Professional's Choice for Professional Results

In the hectic pace of the framing business, BIENFANG® Vacuum Presses are the preferred choice. The vacuum process removes moisture so time isn't lost on pre-drying work. Several pieces of varying size and thickness can be processed simultaneously to speed production. The digital microprocessor technology and touch-pad controls assure quick, efficient and easy operation.



BIENFANG® Vacuum Press Specifications

	3648H	4468H	5298H
Working Capacity	36 x 48 x 1 in. (914.4 x 1219.2 x 25.4 mm)	44 x 68 x 1 in. (1117.6 x 1727.2 x 25.4 mm)	48 x 96 x 1 in. (1219.2 x 2438.4 x 25.4 mm)
Dimensions	56.25w x 47.5d x 6.5h in. (142.9 x 120.7 x 17 cm)	76.25w x 56.5d x 6.5h in. (194 x 144 x 17 cm)	107.25w x 65d x 37.25h in. (273 x 165 x 95 cm)
Net Weight*	130 lb. (59 kg)	205 lb. (92 kg)	375 lb. (170 kg)
Shipping Weight	325 lb. (147 kg)	495 lb. (223 kg)	800 lb. (364 kg)
Power	230 VAC, 11 Amps	230 VAC, 15 Amps	230 VAC, 26 Amps
Requirements	4-wire, single phase NEMA L14-20 plug (230 VAC, 11 Amps, 3-wire)**	4-wire, single phase NEMA L14-20 plug (230 VAC, 15 Amps, 3-wire)**	4-wire, single phase NEMA L14-30 plug (230 VAC, 26 Amps, 3-wire)**
Pressure	13 psi	13 psi	13 psi
Floor Stand	***Optional CUL Listed	***Optional CUL Listed	Built-in CUL Listed

* Vacuum pump weight: 10.5 lb. (5kg)

** International (export) model electrical specifications

***Floor Stand Catalog numbers: 3648H-2167, 4486H-2165

All specifications subject to change without notice.

Bienfang Framing Products

A division of Elmer's Products, Inc.
2020 West Front Street
Statesville, NC 28677

Customer Service: 800-873-4868

Technical Service: 888-240-6021

Tech. Fax: 704-871-8671

Hrs: 8:00 a.m.-5:00 p.m. (EST)

www.elmers.com

www.forframersonly.com

©2007 Elmer's Products, Inc.



Equipment, heat-activated
Adhesives and Foam Board
made in USA.